

Series K2

K-2 Breeze

The K-2 Breeze is designed for high pressure hurricane and water resistance while offering ventilation. The upper panel of the door is fitted with an operable single hung window. SMI's proprietary residential latch lever is standard on all Breeze doors.



K-2 Breeze Door with open window

GENERAL SPECIFICATIONS

PERFORMANCE

- Miami-Dade County protocols – passed
- Design pressure: +90/-120 psf
- Water rating 15 psi

MATERIAL

CHARACTERISTICS

- Aluminum alloy 6063-T6, door components
- Panel Dimensions - Stiles 3-1/2", Bottom Rail 6-1/2", Top Rail 5"
- Stainless steel ball bearing butt hinges with T-6 aluminum backing plates.
- Stainless steel assembly screws
- Glazed with Dow 995 or Pecora 895 structural silicone

OPTIONS

- Aluminum panel over bottom lite
- ADA compliant, water resistant bumper threshold
- Applied muntins

USES

- High rise condominium door
- Residential entrance door

FRAME COLORS

- White, Silver and Bronze in stock.
- Anodized, Kynar and custom powder coat finishes on request.

GLASS TINTS / TEXTURES

- Almost any

SIZES

- Maximum panel size: 3'7" x 8'11-1/2"

◀ **Hurricane and water resistance plus ventilation.**

▼ **Standard proprietary residential latch lever.**



COMMERCIAL RESIDENTIAL



MIAMI-DADE (NOA)
NOTICE
OF ACCEPTANCE

BENEFITS

HIGH DESIGN
PRESSURE

VENTILATION
WINDOW

RESIDENTIAL LATCH
LEVER STANDARD

We Hold Up Under Pressure!