



5000 SERIES FRENCH DOOR

APPROVED FOR THE HVHZ!



Specifications:

Maximum Size	72" x 96" – for double doors 36" X 96"- for single doors
Design Pressure	± 100 for 3' x 8' w/ sill riser ± 75 for 6' x 8' w/ sill riser
Glass	7/16" Impact 1" overall Impact Insulated
Muntin	Flat or Grids on insulated units
Grid Options	Colonial, Prairie, Perimeter
Frame Depth	4 3/4"
Colors	White or Bronze
Testing	TAS 201,202, 203 ASTM E 330, E 1886 – 1996 AAMA/WDMA/CSA 101/I.S/A440-11
HVHZ Approval	Yes

Standard Items:

- **Double Throw-bolt/lock**– engages throw bolts in head and sill and heavy lock in center, all done right from the handle.
- **ADA Sill**– for low clearance

Extra Items:

- **1 1/2" Sill Riser**– add on to obtain a higher design pressure
- **Stainless Steel Components**
- **Insulated Glass**



Features & Benefits:

- **Heavy Walled Construction**– extra heavy duty for real strength
- **Multi-Point Lock**– featuring a double throw bolt design for maximized locking integrity
- **Locking Hardware by Interlock**– high quality!
- **Double Veined Felts**– for quiet operation
- **High Mil Rubber Weather Stripping**– used for tighter seal
- **Stainless Steel Components**– great option to utilize for coastal applications
- **Insulated Glass**– will help provide energy efficiency to help cut down on electric consumption

Maximum Strength Combined With Cost Savings From Proven Energy Efficiency, Gives You The Best Value!

